17—LANDSLIDE AND MASS-WASTING FEATURES

REF NO	DESCRIPTION	SYMBOL	CARTOGRAPHIC SPECIFICATIONS*	NOTES ON USAGE*
17.1	Outline of slip surface of landslide—Identity and existence certain, location accurate		linecolor 60% black lineweight .2 mm VH-8 (60% black)	May be used to outline area of slip surface of landslide if desired.
17.2	Outline of slip surface of landslide—Identity or existence questionable, location accurate	?	≯ 12.0 mm ★	Do not use to outline landslide deposits (use a map-unit boundary contact instead).
17.3	Outline of slip surface of landslide—Identity and existence certain, location approximate		3.5 mm ⇒ ←	contact instead).
17.4	Outline of slip surface of landslide—Identity or existence questionable, location approximate		≯k ≯k .75 mm	
17.5	Outline of slip surface of landslide—Identity and existence certain, location inferred		1.5 mm → k-	
17.6	Outline of slip surface of landslide—Identity or existence questionable, location inferred	?	→ 	
17.7	Outline of slip surface of landslide—Identity and existence certain, location concealed		.5 mm ≯l <	
17.8	Outline of slip surface of landslide—Identity or existence questionable, location concealed	<i>-</i> ?	≯k ≯k .75 mm .75 mm	
17.9	Area of slip surface of landslide		pattern 431-K in 50% black (rotated so lines parallel slip surface [lineweight]	Downslope edge of slip surface is usually con- cealed by landslide
17.10	Direction of downslope movement of landslide	7	direction) 2 mm, in 60% black]	deposits or debris materials. Landslide arrows may be shown singly or in
17.11	Landslide deposits—Arrows show direction of downslope movement		[lineweight .15 mm]	pairs.
17.12	Head or main scarp of landslide—Active, sharp, distinct, and accurately located. Hachures point down scarp		all lineweights .25 mm TTTTTTTTT hachure height 1.0 mm; spacing 1.75 mm	Place line along crown of scarp. May be shown in red or
17.13	Head or main scarp of landslide—Inactive, sub- dued, indistinct, and (or) approximately located. Hachures point down scarp	TTTTTTTT	.5 mm ≯ ←	other colors.
17.14	Head or main scarp of landslide—Showing height (in meters). Hachures point down scarp	0.8	0.8 ² HI-7	
17.15	Head or main scarp of rotated block in landslide— Arrow shows direction of oblique slip. Hachures point down scarp	<u>u</u>	$\begin{array}{c c} 5.0 \\ \hline mm & \\ \hline 15^{\circ} \end{array}$ arrow lineweight .175 mm	
17.16	Internal or minor scarp in landslide—Active, sharp, distinct, and accurately located. Hachures point down scarp		all lineweights .25 mm TTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTT	
17.17	Internal or minor scarp in landslide—Inactive, subdued, indistinct, and (or) approximately located. Hachures point down scarp	ппппппп	.5 mm ⇒ ≮ ППППППП ⇒ ≮2.0 mm	
17.18	Internal or minor scarp in landslide—Showing height (in meters). Hachures point down scarp	0.3	0.3 ~ HI-6	
17.19	Internal or minor scarp of rotated block in landslide —Arrow shows direction of oblique slip. Hachures point down scarp	<u></u>	$ A.5 \leftarrow arrow \\ ineweight \\ .175 \rightarrow k \geq 2.0 \text{ mm}$	

^{*}For more information, see general guidelines on pages A-i to A-v.

17—LANDSLIDE AND MASS-WASTING FEATURES (continued)

			LATOTILS (continued)	
REF NO	DESCRIPTION	SYMBOL	CARTOGRAPHIC SPECIFICATIONS*	NOTES ON USAGE*
17.20	Main toe of landslide—Active, sharp, distinct, and accurately located		3.0 mm \Rightarrow 4.0 mm lineweight .25 mm	Place line along base of toe; sawteeth on over-riding block.
17.21	Main toe of landslide—Inactive, subdued, indistinct, and (or) approximately located	***	.5 mm ⇒ K → K → K → 3.0 mm	May be shown in red or other colors.
17.22	Minor toe, internal thrust fault, or pressure ridge in landslide—Active, sharp, distinct, and accurately located		2.5 mm \Rightarrow \leftarrow \checkmark $\stackrel{60^{\circ}}{\checkmark}$ $\stackrel{1}{\checkmark}$.85 mm lineweight .25 mm	
17.23	Minor toe, internal thrust fault, or pressure ridge in landslide—Inactive, subdued, indistinct, and (or) approximately located	****	.5 mm →	
17.24	Minor toe, internal thrust fault, or pressure ridge in landslide, showing transport reversal—Active, sharp, distinct, and accurately located	* • * • *	lineweight .25 mm $\xrightarrow{1.50}$ $\xrightarrow{1.50}$ $\xrightarrow{1.50}$.85 mm .85 mm	
17.25	Minor toe, internal thrust fault, or pressure ridge in landslide, showing transport reversal—Inactive, subdued, indistinct, and (or) approximately located	*****	.5 mm → K → <-2.0 mm	
17.26	Right flank of landslide or right-lateral shear feature —Active, sharp, distinct, and accurately located		15° ≥ 2.5 mm arrow lineweight .25 mm sineweight .175 mm	Arrow shows sense of lateral movement. Place arrow on side of
17.27	Right flank of landslide or right-lateral shear feature —Inactive, subdued, indistinct, and (or) approximately located		.5 mm → <	moving ground or on displaced earth materials.
17.28	Right flank of landslide or right-lateral shear feature —Concealed by landslide deposits or debris materials		.5 mm → ← .5 mm	In cross section, can also be used to show plane of slope failure. May be shown in red or
17.29	Right flank of landslide or right-lateral shear feature —Showing amount of offset (in meters)	<u>2.3</u>	2.3 ½ HI-7	other colors.
17.30	Left flank of landslide or left-lateral shear feature— Active, sharp, distinct, and accurately located			
17.31	Left flank of landslide or left-lateral shear feature— Inactive, subdued, indistinct, and (or) approxi- mately located		.5 mm → K- →	
17.32	Left flank of landslide or left-lateral shear feature— Concealed by landslide deposits or debris materi- als	<u>4.</u>	.5 mm → k → k .5 mm	
17.33	Left flank of landslide or left-lateral shear feature— Showing amount of offset (in meters)	2.3	2.3 × HI-7	
17.34	Open tension crack or fracture on landslide		hachure height all lineweights .2 mm .5 mm	Hachures point into crack.
17.35	Tension crack or fracture on landslide (1st option)	***************************************	all lineweights .2 mm - - - - - - - - - - - -	May be shown in red or other colors.
17.36	Tension crack or fracture on landslide (2nd option)	<u></u>	all lineweights .2 mm 1.2 *	
17.37	Tension crack or fracture on landslide (3rd option)		lineweight .2 mm	
17.38	En echelon cracks or fractures on landslide, indicating right-lateral shear	m i mu	crack lineweights .2 mm	Arrow shows sense of lateral movement. May be shown in red or
17.39	En echelon cracks or fractures on landslide, indicating left-lateral shear	121111111	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	other colors.
17.40	Anticlinal soft-sediment fold, buckle fold, bulge, or linear ridge on landslide		line length can vary 2.0 mm arrow lineweight 1.75 mm	May be shown in red or other colors.
17.41	Dome structure or bulge on landslide	← ‡→	line length can vary ← ← ← 60° → ← 1.0 mm	
17.42	Synclinal soft-sediment fold or linear depression on landslide	-	lineweight .25 mm $1.0 \text{ mm} \frac{\sqrt{\frac{60^{\circ}}{1.0 \text{ mm}}}}{\sqrt{\frac{1.0 \text{ mm}}{1.0 \text{ mm}}}}$ $\frac{1.0 \text{ mm}}{\sqrt{\frac{1.75 \text{ mm}}{1.75 \text{ mm}}}}$	
17.43	Basin structure or depression on landslide		1.0 mm > line lengths can vary .75 mm > k	

17—LANDSLIDE AND MASS-WASTING FEATURES (continued)

			LATOTILO (continuca)	
REF NO	DESCRIPTION	SYMBOL	CARTOGRAPHIC SPECIFICATIONS*	NOTES ON USAGE*
17.44	Crest line of lateral levee on landslide (1st option)	****	lineweights .175 mm	
17.45	Crest line of lateral levee on landslide (2nd option)	*****	1.0 ½ mm ★ → → → → → ← ← ← ← ← ← ← ← ← ← ← ← ← ←	
17.46	Path of gully on landslide	} 	all lineweights .2 mm 4.5 7 4.5 7 1.575 8 1.575 9 1.575 9 1.575 9 1.575 9 1.575	
17.47	Soil creep or incipient sliding on landslide	~~ ►	lineweight .2 mm 1.0 mm 20° 6.75 mm 1.5 mm	Arrow points downhill. May be shown in red or other colors.
17.48	Spring, seep, or drainage (runoff) on landslide	0~	lineweight .2 mm Cv- circle diameter 1.5 mm; tail length 3.0 mm	Tail points downhill. May be shown in red or other colors.
17.49	Sag pond or closed depression on landslide (mapped to scale)		all lineweights .175 mm hachure height .875 mm; spacing 1.25 mm	Hachures point into depression.
17.50	Hummock on landslide (mapped to scale)	\Diamond	all lineweights .175 mm .875 mm, spacing 1.25 mm	Hachures point away from hummock.
17.51	Hummock on landslide (shown as point symbol when too small to outline at map scale)	₩	all lineweights .175 mm 60° 875 circle diameter 1.5 mm	
17.52	Tilt direction of surface of landslide	\Rightarrow	4.0 mm	Usually shown on special-purpose land-slide activity maps.
17.53	Tilt direction of surface of landslide—Showing angle of tilt	□ > ¹⁴	□ 14 ← HI-6	May also be shown in red or other colors.
17.54	Displacement vector—Showing bearing	\longrightarrow	lineweight .2 mm	
17.55	Displacement vector—Showing bearing and distance	—————————————————————————————————————	1.3 ^{← HI-7}	
17.56	Active, reactivated, or historically active debris flow, showing a sharply defined morphology	V		Usually shown on special-purpose land-slide activity maps.
17.57	Dormant-young debris flow, showing a fresh and uneroded morphology but having no evidence of historic activity	T	color 50% magenta	If necessary, alpha- numeric characters may be added to help distin-
17.58	Active, reactivated, or historically active landslide (mapped to scale), showing a sharply defined morphology		fill color 60% magenta	guish landslide areas. May also be shown in red or other colors.
17.59	Dormant-young landslide (mapped to scale), show- ing a fresh and uneroded morphology but having no evidence of historic activity		fill color 40% magenta	
17.60	Dormant-mature landslide (mapped to scale), showing a smoothed and eroded morphology		fill color 20% magenta	
17.61	Dormant-old or relict landslide (mapped to scale), showing a weak morphology		fill color 8% magenta	
17.62	Rock slide, slump, block-glide landslide, rotational landslide, or Toreva block, consisting of a relatively intact mass of displaced materials	K	draft as shown draft as shown √ 90° all lineweights 3 mm	Usually shown on special-purpose land-slide activity maps.
17.63	Earth flow, consisting of a relatively thick and jumbled mixture of displaced materials	\downarrow	★ ★ 1.0 mm 4.5 mm All lineweights → 30° 3 mm	May also be shown in red or other colors. If necessary, symbols
17.64	Debris slide, consisting of a loose and relatively shallow veneer of displaced materials	\$	draft as shown 90° all lineweights .3 mm	may be enlarged or reduced.
17.65	Debris-slide slope (mapped to scale), consisting of coalesced scars of landslides and debris flows that are too small or numerous to be shown at map scale		fill color 20% black	Usually shown on special-purpose land-slide activity maps.

*For more information, see general guidelines on pages A-i to A-v.